

# **Technical Data Sheet**

# **Clarion Material Code T**

#### **Primary Use**

The Clarion T material is manufactured using anodized natural aluminum with text and images dyed and sealed. It is primarily used for product safety labeling placed in a high temperature environment but is suitable for a variety of applications where a high temperature application is a requirement. Such applications include but are not limited to rating plates, property ID and asset labeling, warning, instruction, service labels and nameplates for durable goods. The use of the 3M high temperature acrylic adhesive provides a strong bond and has exceptional degree of humidity, chemical, and solvent resistance.

#### **Base Materials**

.005 anodized aluminum

#### **Adhesive Backing**

3M .002 Premium High Temperature Acrylic

#### **Standard Sizes**

Standard label sizes available as well as almost any custom size

### **Outdoor Durability**

Excellent

### **Water Resistance**

Excellent

### **Chemical Resistance**

Excellent

#### **Storage Stability**

Stable. Optimum storage conditions: 72°F @ 50% relative humidity

#### **Temperature Resistance**

Rated -40°F to 450°F (continuous or frequent exposure to temperatures in excess of 200°F may result in color fade and yellowing.)

#### **Installation Temperature**

50°F or higher

#### **Specification Compliance**

Clarion standard safety colors meet *ANSI Z535.1-2022 Standard for Safety Colors requirements.* (Exact colors may vary slightly due to the anodized aluminum substrate)





©Clarion, All Rights Reserved



1



**Country of Origin: USA** 

# Expected Life

Indoor: Long term

Outdoor: 5-7 years (expected outdoor life may vary due to climatic conditions)

#### Shelf Life:

This material will retain its performance and properties for forty-eight (48) months (4 years) from date of manufacture if properly stored at room temperature conditions of 72°F (22°C) and 50% relative humidity. (All Clarion safety labels are shipped in high quality 4 mil. zip-locked sealed bags for improved storage.)

#### **Product Information**

This technical product information is based upon information provided to Clarion by its suppliers of the raw materials we use to manufacture our products. As such Clarion makes no independent representations or warranties, expressed or implied, and assumes no liability in connection with the use of this information.

#### Warranty

Clarion products are sold with the understanding that the buyers will test them in actual use and determine for themselves whether or not the materials meet their intended use requirements. Clarion warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Clarion's satisfaction to have been defective at the time Clarion sold it. This warranty does not extend to any persons obtaining the product from buyers. This warranty is in lieu of any other warranty, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on clarion's part, Under no circumstances will Clarion be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Clarion's products.

